



FLOODLIGHTS

SYLVANIA

615 Sylveo LED



619 Sylveo



623 Start Flood



627 FloodLED



630 FEH LED



631 FEH



632 Sylflood



635 Archflood



639 Powerflood



642 FMD





EVO

LED RANGE



Control gear: Electronic
Housing: Die-cast aluminium
Protection: High protection class: IP66, Heavy-duty housing: IK08

- The new Sylveo LED is a full range of outdoor & indoor LED floodlights to replace traditional HID
- The floodlights are perfect for lighting industrial areas, parking areas, building facades, billboards and small recreational facilities
- Sylveo LED comes in 5 sizes: Small, Medium, Large, Extra large and Extra extra large
- It is also available in narrow, wide or asymmetric beam angles - offering you a wide selection depending on the required application
- Sylveo LED not only delivers high performance: up to 30,412lm (luminaire lumen output on Sylveo Extra Extra large 4,000K version); but also high efficiency: up to 109lm/W (total system efficiency on Sylveo LED Large 4,000K version)
- All EVO LED range items will be identified with the EVO range yellow flag

Sylveo LED



Sylveo LED - Small



Sylveo LED - Medium



Sylveo LED - Large



Sylveo LED - Extra large



Sylveo LED - Extra extra large


- A full range of outdoor & indoor LED floodlights to replace traditional HID
- Comes in 5 sizes: small, medium, large, extra large and extra extra large
- Narrow, wide or asymmetric beam angles
- Neutral white (4,000K) or warm white (3,000K)
- High performance: delivers up to 30,412lm (luminaire lumen output on Sylveo Extra Extra large 4,000K version)
- High efficiency: delivers up to 109lm/W (total system efficiency on Sylveo LED Large 4,000K version)
- High efficient thermal design: ta -45°C - +45°C
- Slim profile assures ease of installation
- Cable included with the product so no need to open the gear box during installation
- Comes complete with an adjustable bracket for mounting
- Universal pole top adapter available as an accessory for small, medium and large floodlights
- Long lifetime: 50,000 hours life
- Energy class: A++, A+, A
- All EVO LED range items will be identified with the EVO range yellow flag

3,000K


Code	Description
Small	
0049103	SYLVEO LED 3000LM NAR 3K
0049104	SYLVEO LED 3000LM WIDE 3K
0049105	SYLVEO LED 3000LM ASYM 3K
Medium	
0049109	SYLVEO LED 8000LM NAR 3K
0049110	SYLVEO LED 8000LM WIDE 3K
0049111	SYLVEO LED 8000LM ASYM 3K
Large	
0049115	SYLVEO LED 12000LM NAR 3K
0049116	SYLVEO LED 12000LM WIDE 3K
0049117	SYLVEO LED 12000LM ASYM 3K
Extra large	
0049121	SYLVEO LED 20000LM NAR 3K
0049122	SYLVEO LED 20000LM WIDE 3K
0049123	SYLVEO LED 20000LM ASYM 3K
Extra Extra large	
0049127	SYLVEO LED 30000LM NAR 3K
0049128	SYLVEO LED 30000LM WIDE 3K
0049129	SYLVEO LED 30000LM ASYM 3K

Legend: 3K = 3,000K warm white; WIDE = WIDE beam; ASYM; ASYMmetric beam; NAR = NARrow beam


LIGHT SOURCE INCLUDED




Small wide beam 3,000K neutral white




Small Asymmetric beam 3,000K neutral white




Medium wide beam 3,000K neutral white




Medium Asymmetric beam 3,000K neutral white




Large wide beam 3,000K neutral white




Large Asymmetric beam 3,000K neutral white




Extra large wide beam 3,000K neutral white




Extra large Asymmetric beam 3,000K neutral white



Extra extra large wide beam 3,000K neutral white



Extra extra large Asymmetric beam 3,000K neutral white





Sylveo LED - Small

4,000K

Code Description

Small

0049100	SYLVEO LED 3000LM NAR 4K
0049101	SYLVEO LED 3000LM WIDE 4K
0049102	SYLVEO LED 3000LM ASYM 4K

Medium

0049106	SYLVEO LED 8000LM NAR 4K
0049107	SYLVEO LED 8000LM WIDE 4K
0049108	SYLVEO LED 8000LM ASYM 4K

Large

0049112	SYLVEO LED 12000LM NAR 4K
0049113	SYLVEO LED 12000LM WIDE 4K
0049114	SYLVEO LED 12000LM ASYM 4K

Extra large

0049118	SYLVEO LED 20000LM NAR 4K
0049119	SYLVEO LED 20000LM WIDE 4K
0049120	SYLVEO LED 20000LM ASYM 4K

Extra Extra large


0049124	SYLVEO LED 30000LM NAR 4K
0049125	SYLVEO LED 30000LM WIDE 4K
0049126	SYLVEO LED 30000LM ASYM 4K

Legend: 4K = 4,000K Neutral White; WIDE = WIDE beam; ASYM; ASYMetric beam; NAR = NARrow beam


LIGHT SOURCE INCLUDED




EVO
LED RANGE




Small wide beam 4,000K neutral white




Small Asymmetric beam 4,000K neutral white




Medium wide beam 4,000K neutral white




Medium Asymmetric beam 4,000K neutral white




Large wide beam 4,000K neutral white




Large Asymmetric beam 4,000K neutral white




Extra large wide beam 4,000K neutral white



Extra large Asymmetric beam 4,000K neutral white




Extra extra large wide beam 4,000K neutral white




Extra extra large Asymmetric beam 4,000K neutral white


Sylveo LED - Small




Sylveo LED - Medium




Sylveo LED - Large



Sylveo LED - Extra large



Sylveo LED - Extra extra large







Control Gear: Magnetic
Housing: Die-cast aluminium
Finish: Grey
Protection: IP65 and IK08

- 70W to 400W floodlight range covering most requirements: Flood / Wide, Spot / Narrow and Asymmetric reflectors
- The range of luminaires offers a variety of different lamp types giving you the freedom to create the perfect light for various applications
- Fit for all indoor and outdoor lighting projects

Sylveo



- 5mm toughened glass and silicon gaskets ensures IP65 protection
- Gore-Tex® screw-in vent constantly allows the floodlight to breathe with changing environmental conditions, avoiding condensation to develop in the unit
- Developed specifically for exterior environments:
 - Running temperature from -30°C to +40°C
 - Wind exposed surface 0.11m²
 - Galvanised steel bracket, secured with stainless steel M10 screws
 - Goniometers in polyamide PA66 ensures a precise tilt
- Glass sturdily held in place with two adjustable clips at the top, and two rotary anti-loss hinges support at the bottom
- High optical performance for external use



Narrow

Code **Description**

150W
0039801 Sylveo 1 HSI-TD 150W

Wide

Code **Description**

70W
0039805 Sylveo 1 HSI-TD 70W
0039807 Sylveo 1 SHP-TS 70W

100W
0039809 Sylveo 1 HSI-MP 100W

150W
0039806 Sylveo 1 HSI-TD 150W
0039808 Sylveo 1 SHP-TS 150W

Asymmetric

Code **Description**

70W
0039810 Sylveo 1 HSI-TD 70W

150W
0039811 Sylveo 1 HSI-TD 150W
0039813 Sylveo 1 SHP-TS 150W

LIGHT SOURCE INCLUDED



HSI-TD MetalArc WDL
70/150W Rx7s / Rx7s-24
5500/12500lm



SHP-S TwinArc
70W E27 6000lm




HSI-MP MetalArc WDL
70/100/150W E27
5500/8500/13000lm


HSI-TD MetalArc NDL
70/150W Rx7s / Rx7s-24
5800/12500lm




SHP-S TwinArc
150W E40 15500lm




Narrow Beam



Wide Beam



Asymmetric Beam




Protective grid



Universal Pole Clamp

Accessories

Code **Description**
0039835 Protective grid
0039837 Universal Pole clamp



Dimensions (mm)



- 5mm toughened glass and silicon gaskets ensures IP65 protection
- Gore-Tex® screw-in vent constantly allows the floodlight to breathe with changing environmental conditions, avoiding condensation to develop in the unit
- Developed specifically for exterior environments:
 - Running temperature from -30°C to +40°C
 - Wind exposed surface 0.11m²
 - Galvanised steel bracket, secured with stainless steel M10 screws
 - Goniometers in polyamide PA66 ensures a precise tilt
- Glass sturdily held in place with two adjustable clips at the top, and two rotary anti-loss hinges support at the bottom
- High optical performance for external use

LIGHT SOURCE INCLUDED



HSI-HX
250/400W E40
23000/37000lm

SHP-S TwinArc
250/400W E40
30000/52500lm





Narrow

Code **Description**

400W

0039821 Sylveo 2 HSI-TSX 400W

0039823 Sylveo 2 SHP-TS 400W



Narrow beam

Wide

Code **Description**

250W



0039824 Sylveo 2 HSI-TSX 250W

0039826 Sylveo 2 SHP-TS 250W

400W

0039825 Sylveo 2 HSI-TSX 400W

0039827 Sylveo 2 SHP-TS 400W



Wide beam

Asymmetric

Code **Description**

250W



0039828 Sylveo 2 HSI-TSX 250W

0039830 Sylveo 2 SHP-TS 250W


400W

0039829 Sylveo 2 HSI-TSX 400W


0039831 Sylveo 2 SHP-TS 400W



Asymmetric beam



Dimensions (mm)



Protective grid



Universal Pole Clamp

Accessories

Code **Description**

0039838 Protective grid

0039837 Universal pole clamp



EVO

LED RANGE



Control Gear: Electronic - integrated LED driver
Housing: Die-cast aluminium
Finish: Black
Protection: IK07; Floodlight IP65 and PIR IP44

- The new Start Flood range of exterior LED floodlights incorporates the latest high powered COB LED technology into a slimline die-cast aluminium body
- The standard floodlight version is IP65 weatherproof (PIR IP44) and is available in both 3,000K and 4,000K
- All products include 1m stripped cable making the product quick to install while the PIR version comes with a 8m range and 120° detection angle

Start Flood



Start Flood



LED Floodlight with PIR



Slimline floodlight

- Slimline exterior LED floodlight with / without PIR
- Ideal for residential or small office / warehouse applications
- Durable die-cast aluminium body with tilting bracket
- PIR range is 8m with 120 degree detection angle
- Floodlight versions with PIR come with adjustable lux (0-1000 lux) and time levels (10 sec-12 min)
- Direct replacement for energy inefficient Halogen R7s (10W = 48W / 26W = 120W / 50W = 230W)
- High lumen efficacy of up to 94lm/W
- Quick and easy to install as includes 1m pre-wired stripped cable and fittings
- Energy class: A++, A+, A
- Long lifetime: 30,000 hours life at 70% of the original output L70

3,000K

Code	Description
10W	
0047830	START FLOOD LED 800LM 10W 3000K
0047832	START FLOOD LED 800LM 10W PIR 3000K
26W	
0047822	START FLOOD LED 2100LM 26W 3000K
0047824	START FLOOD LED 2100LM 26W PIR 3000K
50W	
0047826	START FLOOD LED 4400LM 50W 3000K
0047828	START FLOOD LED 4400LM 50W PIR 3000K


4,000K

Code	Description
10W	
0047831	START FLOOD LED 850LM 10W 4000K
0047833	START FLOOD LED 850LM 10W PIR 4000K
26W	
0047823	START FLOOD LED 2300LM 26W 4000K
0047825	START FLOOD LED 2300LM 26W PIR 4000K
50W	
0047827	START FLOOD LED 4700LM 50W 4000K
0047829	START FLOOD LED 4700LM 50W PIR 4000K

LIGHT SOURCE INCLUDED




*PIR version




3,000K - 10W

4,000K - 10W



3,000K - 26W

4,000K - 26W




3,000K - 50W

4,000K - 50W


Dimensions (mm)

Floodlight with PIR (IP44)	A	B	C	D
10W	171	131.3	150	61.1
26W	213	181.1	181.1	69
50W	268.3	220.6	220.6	82



Dimensions (mm)

Floodlight (IP65)	A	B	C	D
10W	149	113	122	49.3
26W	194.5	151.3	180	59.5
50W	268.3	220.7	220.7	70.8









Control Gear: Electronic - integrated LED driver
Housing: Die-cast aluminium
Finish: Grey, RAL9007
Protection: IP65 and IK08

- FloodLED is a versatile range of LED-based floodlights suited for medium and small scale lighting projects
- Their high performance lies in their ultra-thin, rugged design
- The range offers choice between 3 colour temperatures and 2 beam angles

FloodLED


FloodLED 48

SYLVANIA




- Up to 6,000 Lumens
- 80W LED luminaire
- Ultraflat housing
- High efficient thermal design: ta -30°C - +60°C
- Tight binning selection of LEDs: CRI 75-80
- 3 light temperatures:
 - 3,000K warm white
 - 4,000K neutral white
 - 6,500K cool white
- Wide beam angle at 42°
- Energy saving LED luminaire: up to 70lm/W

LIGHT SOURCE INCLUDED




Wide beam


Code	Description
0047715	FloodLED 48 6,500K Wide
0047737	FloodLED 48 4,000K Wide
0047738	FloodLED 48 3,000K Wide



42° Wide Beam



Wide Beam



Accessories



Universal Pole Clamp

Accessories


Code	Description
0039837	Universal Pole Clamp






- Up to 1,700 Lumens
- 25W LED luminaire
- Ultraflat housing
- High efficient thermal design: ta -30°C - +60°C
- Tight binning selection of LEDs: CRI 75-80
- 3 light temperatures:
 - 3,000K warm white
 - 4,000K neutral white
 - 6,500K cool white
- Wide beam angle at 42°
- Energy saving LED luminaire: up to 65lm/W

LIGHT SOURCE INCLUDED




Wide beam

Code	Description
0047703	FloodLED 12 6,500K Wide
0047729	FloodLED 12 4,000K Wide
0047730	FloodLED 12 3,000K Wide




42° Wide Beam




Wide Beam

Front View




Dimensions (mm)

Side View



Top View



Accessories

Code	Description
0039837	Universal Pole Clamp



Universal Pole Clamp





FEH LED




FEH LED - Back view



- 86W LED floodlight
- FEH LED is a versatile LED indoor & outdoor floodlight particularly suited to medium to small scale exterior lighting projects
- High performance: delivers 5,574lm (luminaire lumen output on 3,000K version), equating to 65lm/W (total system efficiency)
- 30 x 60° beam angle
- Retro-looking housing
- Available in Warm white (3,000K)
- High efficient thermal design: ta -30°C - +40°C
- Tight binning selection of LEDs: CRI 85
- High protection class: IP65
- Heavy-duty die-cast housing: IK07
- Easy to adjust lighting angle thanks to the turn and tilt scale
- Long lifetime: 50,000 hours life at 70% of the original output L70
- Less maintenance is required due to the long lifetime of 50,000hrs
- Energy Class: A++, A+, A

LIGHT SOURCE INCLUDED




FEH LED - 3,000K

FEH LED



Code	Description
0047749	FEH LED 30 x 60° 3,000K

Front view



Dimensions (mm)

Back view



Legend: Bloemen Thomas - Kuringen, Belgium



FEH 500W



FEH 1,000W


Dimensions (mm)

	L	P	H	Weight (kg)
FEH 500W	205	265	250	3.00
FEH 1,000W	275	265	250	3.30
FEH 1,500W	340	265	250	3.70
FEH 2,000W	455	265	250	5

- Robust die-cast and streamlined aluminium body
- High optical performance for external use
- Wind exposed surface 0.18m²

FEH


Code	Description
0043180	FEH 500W R7s NOT LAMPED
0043181	FEH 1,000W R7s NOT LAMPED
0043182	FEH 1,500W R7s NOT LAMPED
0043583	FEH 2,000W R7s NOT LAMPED




LIGHT SOURCE NOT INCLUDED




HDE QT-DE12
500/1000/1500/2000W R7s
9250/22000/33000/44000lm



HDE - 500W



HDE - 1,000W




HDE - 2,000W

Accessories



Visor



Protective grid

Visor Accessory

Code	Description
0043196	3 SIDED SCREEN FOR FEH500

Protective grid Accessory

Code	Description
0043200	GUARD GRILL FEH500
0043201	GUARD GRILL FEH1000



Gallo-Roman Museum - Tongeren, Belgium



Sylflood 1



Sylflood 2

- High photometric performance
- Range suitable for the majority of outdoor applications
- Luminaire comes complete, including ballast and lamp
- Direct access to the lamp and the ballast


Sylflood 1

Code	Description
Extensive	
0039910	SYLFLOOD 1 Extensive + bulb HSI-TD 70W 4K
0039911	SYLFLOOD 1 Extensive + bulb HSI-TD 150W 4K
Asymmetric	
0039912	SYLFLOOD 1 Asymmetric + bulb HSI-TD 70W 4K
0039913	SYLFLOOD 1 Asymmetric + bulb HSI-TD 150W 4K

Sylflood 2

Code	Description
Extensive	
0039920	SYLFLOOD 2 Extensive + bulb SHP-TS 250W
0039924	SYLFLOOD 2 Extensive + bulb HSI-THX 250W
0039921	SYLFLOOD 2 Extensive + bulb SHP-TS 400W
0039925	SYLFLOOD 2 Extensive + bulb HSI-THX 400W
0039907	SYLFLOOD 2 Extensive + bulb HSI-TSX 400W
Asymmetric	
0039922	SYLFLOOD 2 Asymmetric + bulb SHP-TS 250W
0039926	SYLFLOOD 2 Asymmetric + bulb HSI-THX 250W
0039908	SYLFLOOD 2 Asymmetric + bulb HSI-TSX 250W
0039923	SYLFLOOD 2 Asymmetric + bulb SHP-TS 400W
0039927	SYLFLOOD 2 Asymmetric + bulb HSI-THX 400W
0039909	SYLFLOOD 2 Asymmetric + bulb HSI-TSX 400W

LIGHT SOURCE INCLUDED



HSI-TD Metalarc WDL
70/150W Rx7s / Rx7s-24
5500/12500lm




HSI-TD Metalarc NDL
70/150W Rx7s / Rx7s-24
5800/12500lm




SHP-S TwinArc
250/400W E40 30000/52500lm




HSI-HX
250/400W E40 23000/37000lm




Sylflood 1 Extensive - HSI-TD - 150W




Sylflood 1 Asymmetric - HSI-TD - 150W



Sylflood 2 Extensive - HSI-THX - 400W



Sylflood 2 Asymmetric - HSI-THX - 400W









Control Gear: Magnetic
Housing: Die-cast aluminium
Finish: Grey, RAL9007
Protection: IP65 and IK08

- Range of 10 HID-based floodlights
- Archflood provides specifiers with maximum flexibility depending on project / application on hand
- All-weather construction is designed for easy aiming, simple cleaning and quick maintenance

Archflood



- 250W and 400W luminaire
- Fully integrated control gear
- Narrow light beam at 8° as standard
- Adjustable lighting angle using tilt and turn features
- High quality tempered glass
- High efficiency pure aluminium reflector



400W	
Code	Description
0049305	Archflood 1 Grey Narrow 400W E40 Magnetic Gear

250W	
Code	Description
0049306	Archflood 1 Grey Narrow 250W E40 Magnetic Gear


LIGHT SOURCE NOT INCLUDED




HSI-SX CL/P
250/400W E40 21000/42000lm




SHP-S TwinArc
250/400W E40 30000/52500lm



8° Narrow Standard Beam



Narrow Beam



Dimensions (mm)

Accessories



Antiglare Shield



Universal Pole Clamp

Accessories


Code	Description
0049307	Archflood 1 Grey Antiglare Shields
0039837	Universal Pole Clamp






- 70W luminaire
- Narrow beam at 8°
- Adjustable lighting angle using tilt and turn features
- High quality tempered glass
- High efficiency pure aluminium reflector
- Fully integrated control gear

LIGHT SOURCE NOT INCLUDED





CMI-T WDL/ ND
70W G12 6700lm




70W

Code	Description
0049323	Archflood 3 Grey Narrow 70W G12 Magnetic Gear



8° Narrow Standard Beam



Narrow Beam

Accessories



Antiglare Shield



Lens Wide Redial

Accessories

Code	Description
0049335	Archflood 3 Grey Antiglare Shield
0049337	Archflood 3 Lens wide radial max 70W





Control Gear: Magnetic
Housing: Die-cast aluminium
Finish: Grey, RAL9007
Protection: IP65 and IK08

- High performance general performance floodlight
- Illuminates facades, sports halls / grounds
- Luminaire distributes narrow, wide or extra wide beam evenly, accurately and efficiently

Powerflood



Powerflood 1 - Narrow



Powerflood 1 - Wide



Powerflood 1 - Extra wide



- 1,000W and 2,000W luminaire
 - Rear access for easy lamp replacement
 - Beams at 18°, 29° and 36°
 - Adjustable lighting angle using tilt and turn features
 - High quality tempered glass
 - Protective front mesh
- External gear boxes needed to be ordered separately*

LIGHT SOURCE NOT INCLUDED



HSI-TD
1000/2000W Cable
90000/200000lm

Narrow


Code	Description	Beam Angle (°)
0049380	Powerflood 1 Grey Narrow 1,000W HSI-TD	18
0049381	Powerflood 1 Grey Narrow 2,000W HSI-TD	18

Wide


Code	Description	Beam Angle (°)
0049382	Powerflood 1 Grey Wide 1,000W HSI-TD	29
0049383	Powerflood 1 Grey Wide 2,000W HSI-TD	29

Extra Wide


Code	Description	Beam Angle (°)
0049384	Powerflood 1 Grey Extra Wide 1,000W HSI-TD	36
0049385	Powerflood 1 Grey Extra Wide 2,000W HSI-TD	36




18° Narrow Beam




29° Wide Beam




36° Extra Wide Beam





Narrow Beam



Wide Beam



Extra Wide Beam



Dimensions (mm)

Accessories



Universal Pole Clamp



External Gear Tray

Accessories

Code	Description
0049386	Powerflood External Gear Tray 1,000W
0049387	Powerflood External Gear Tray 2,000W
0039837	Universal Pole Clamp




Melico Salazar Theatre, San José, Costa Rica



FMD Asymmetrical

- Easy to install and maintain
- Choice of reflectors: narrow or wide
- Asymmetrical distribution

LIGHT SOURCE NOT INCLUDED



HSI-T
1000/2000W E40 80000/200000lm



9058350




9058351

FMD 1,000W / 2,000W - Asymmetrical

Code	Description
0039449	FMD ASYM 1,000W E40 NO LAMP EXT.GEAR REQ
0039450	FMD ASYM 2,000W E40 NO LAMP EXT.GEAR REQ

Gear tray

Code	Description
9058350	GT HPS 1,000W 230V for SHP-S Lamp
9058351	GT MH 1,000W 230V for HSI-THX Lamp
9058352	GT MH 2,000W 380V (usable with and without ignitor) for HSI-TS lamp




FMD Asymmetrical - HSI-TX - 1,000W

Dimensions (mm)

	L	I	P1	P2	H	Weight (kg)
0039449	560	490	445	220	560	13
0039450	680	870	560	410	1,000	30

FMD 1,000 AS
3 holes Ø25mm



FMD 1,000 AS
3 holes Ø10mm
FMD 1,000
3 holes Ø10mm
FMD 2,000
5 holes Ø16.5mm

